

OPTIMIZATION OF STAND-ALONE PHOTOVOLTAIC SYSTEM BY
IMPLEMENTING FUZZY LOGIC MPPT CONTROLLER

MOKHTAR BIN HASHIM

A project report submitted in partial
fulfillment of the requirement for the award of the
Degree of Master of Electrical Engineering

Faculty of Electrical and Electronic Engineering
Universiti Tun Hussein Onn Malaysia

JULY, 2013

For my beloved mother, wife, son and daughter



ACKNOWLEDGEMENT

First and foremost, I would like to thank the almighty God (ALLAH) for blessing and guiding me through all the difficult stages of my life until to this point. Without this guidance I would never to complete my master's project successfully.

I am deeply indebted to my supervisor Dr. Wahyu Mulyo Utomo for guiding me and encouraging me throughout the project. With such fully of knowledge's, experience and dedication, he provided the very good direction, opinion and committed which led me on the right position. I am very grateful to have such a kindness and supportive supervisor during the process to complete these studies.

My sincere thanks also go to my mother Rosnah Binti Hamid. I owe my loving thank to my wife Sarihat Binti Kamaruddin for being a very understanding wife, and patience to support me all the time. Without their encouragement and advice, it would be quite tough for me to complete this work.

To my beloved son and daughter, Muhamad Dzikry Ilmi, and Nur Amni Khairani for making my life so enjoyable and meaningful. Without their encouragement and support, it would be quite tough for me to complete this thesis.

I warmly thank to all friend for a valuable advice, constructive comments and being a wonderful friend throughout this work.

Finally, I also wish to thank all postgraduate member, all staff in Faculty of Electrical Engineering and Postgraduate Centre for their support, cooperation and contribution all the way. Universiti Tun Hussein Onn Malaysia (UTHM) is gratefully acknowledged.

Thank you so much.

ABSTRACT

A photovoltaic (PV) generator is a nonlinear device having insolation-dependent volt-ampere characteristics. Since the maximum-power point varies with solar insolation, it is difficult to achieve an optimum matching that is valid for all insolation levels. Thus, Maximum power point tracking (MPPT) plays an important roles in photovoltaic (PV) power systems because it maximize the power output from a PV system for a given set of condition, and therefore maximize their array efficiency. This project presents a maximum power point tracker (MPPT) using Fuzzy Logic theory for a PV system. The work is focused on a comparative study between most conventional controller namely Perturb and Observe (P&O) algorithm and is compared to a design fuzzy logic controller (FLC). The introduction of fuzzy controller has given very good performance on whatever the parametric variation of the system.

ABSTRAK

Penjana photovoltaic (PV) adalah sejenis peranti tidak lurus yang mempunyai spesifikasi volt-ampere yang bergantung kepada ketumpatan sinaran matahari. Oleh kerana titik maksimum kuasa berubah-ubah mengikut kecerahan sinaran matahari, maka ia adalah sukar untuk mencapai nilai padanan maksimum yang sah untuk setiap peringkat kecerahan. Oleh itu, pengesanan titik kuasa maksimum (MPPT) memainkan peranan penting dalam system kuasa photovoltaic (PV) kerana ia dapat memaksimumkan kuasa keluaran dari sistem PV untuk satu set keadaan dan seterusnya memaksimumkan kecekapan tatasusunan PV tersebut. Projek ini mempersembahkan satu pengesanan titik kuasa maksimum (MPPT) yang menggunakan teori fuzzy logic untuk sistem PV. Kerja-kerja ini memfokuskan kepada satu kajian perbandingan antara pegawal paling konvensional iaitu P&O algoritma dan dibandingkan dengan rekabentuk pengawal fuzzy logic (FLC). Pengenaln kepada pengawal fuzzy logic telah memberikan prestasi yang sangat baik dalam apa sahaja perubahan parameter system tersebut.

CONTENTS

| | | |
|------------------|---|------------|
| | TITLE | i |
| | DECLARATION | ii |
| | DIDICATION | iii |
| | ACKNOWLEDGEMENT | iv |
| | ABSTRACT | v |
| | CONTENTS | vii |
| | LIST OF TABLES | x |
| | LIST OF FIGURES | xi |
| CHAPTER 1 | INTRODUCTION | 1 |
| | 1.1 Motivation | 1 |
| | 1.2 Project Background | 2 |
| | 1.2.1 PV Equivalent Circuit | 3 |
| | 1.2.2 PV Module Characteristic | 4 |
| | 1.2.3 Need for Maximum Power Tracking | 5 |
| | 1.2.4 How Maximum Power Point is Obtain | 8 |
| | 1.2.5 Methods of Peak Power Tracking | 9 |
| | 1.3 Problem Statement | 10 |
| | 1.4 Project Objectives | 11 |
| | 1.5 Project Scopes | 12 |
| CHAPTER 2 | LITERATURE REVIEW | 13 |

| | | |
|------------------|--|-----------|
| CHAPTER 3 | METHODOLOGY | 18 |
| 3.1 | Modelling PV Devices | 18 |
| 3.2 | Modelling of DC-DC Boost Converter | 25 |
| 3.2.1 | Boost Converter and It Operation | 25 |
| 3.2.2 | Design of The Boost Converter | 28 |
| 3.3 | MPPT algorithm used for simulation in Matlab ^R /Simulink ^R . | 30 |
| 3.3.1 | Perturb and Observation (P&O) | 30 |
| 3.3.2 | Fuzzy Logic MPPT Controller | 32 |
| CHAPTER 4 | SIMULATION AND RESULTS | 34 |
| 4.1 | Simulink Model of PV Devices | 34 |
| 4.1.1 | Simulink model of the new calculated current | 35 |
| 4.1.2 | Simulink model of diode saturation current (Io) | 35 |
| 4.1.3 | Simulink model of nominal saturation current (Ion) | 36 |
| 4.1.4 | Simulink model of PV module | 36 |
| 4.1.5 | Simulation result of PV module characteristic curve. | 37 |
| 4.2 | Simulation result of PV module is directly connected to resistive load | 39 |
| 4.3 | Simulation result for BP SX 150 PV module coupled with boost converter and the P&O MPPT algorithm. | 41 |
| 4.4 | Simulation comparison between the P&O MPPT algorithm and Fuzzy Logic MPPT controller. | 44 |

| | | | |
|----------------|----------|--------------------------------------|-----------|
| CHAPTER | 5 | CONCLUSION AND RECOMMENDATION | 46 |
| | 5.1 | Conclusion | 46 |
| | 5.2 | Recommendation | 47 |
| | | REFERENCES | 48 |



LIST OF TABLES

| | | |
|-----|---|----|
| 3.0 | Fuzzy logic controller rules base | 33 |
| 4.0 | Electrical characteristics data of PV module taken from the datasheet | 35 |



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF FIGURES

| | | |
|-----|---|----|
| 1.0 | Typical diagram of MPPT in a PV System | 2 |
| 1.1 | Typical circuit of PV solar cell | 3 |
| 1.2 | Characteristics of a typical solar PV module | 5 |
| 1.3 | Changes in the characteristics of the solar pv module due to change in insolation level. | 6 |
| 1.4 | Change in the module characteristics due to the change in temperature | 7 |
| 1.5 | Block diagram of a typical MPPT system | 7 |
| 1.6 | DC/DC converter helps in tracking the peak power point | 9 |
| 1.7 | PV module is directly connected to a (variable) resistive load. | 10 |
| 1.8 | I-V curve of PV module and various resistive load | 11 |
| 3.0 | The equivalent circuit of the Practical photovoltaic cell | 18 |
| 3.1 | Characteristic I - V curve of the PV cell. The net cell current I is composed of the light-generated current I_{pv} and the diode current I_d . | 19 |
| 3.2 | Characteristic I - V curve of a practical PV device and the three remarkable points: short circuit (0, I_{sc}), MPP (V_{mp} , I_{mp}), and open circuit (V_{oc} , 0). | 22 |
| 3.3 | Physical structure of a PV cell. | 22 |
| 4.4 | Circuit diagram of boost converter | 25 |
| 3.5 | The OFF state diagram of the boost converter | 26 |
| 3.6 | The ON state diagram of the boost converter | 26 |
| 3.7 | Inductor current waveform | 27 |
| 3.8 | Inductor voltage waveform | 27 |

| | | |
|------|---|----|
| 3.9 | Perturb and Observation (P&O) Flow Chart | 31 |
| 3.10 | Fuzzy logic controller design | 32 |
| 4.0 | Picture of BP SX 150S PV module | 34 |
| 4.1 | Simulink model of new calculated current | 35 |
| 4.2 | Simulink model of diode saturation current (I_o) | 35 |
| 4.3 | Simulink model of nominal saturation current (I_{on}) | 36 |
| 4.4 | Simulink model PV modules | 36 |
| 4.5 | I-V curves of BP SX 150S PV module at various irradiances and simulated with temperature 25°C. | 37 |
| 4.6 | P-V curves of BP SX 150S PV module at various irradiances and simulated with temperature 25°C | 37 |
| 4.7 | I-V curves of BP SX 150S PV module at various temperatures and simulated with irradiance 1000 W/m ² . | 38 |
| 4.8 | P-V curves of BP SX 150S PV module at various temperatures and simulated with irradiance 1000 W/m ² . | 38 |
| 4.9 | Simulink model of PV module is directly connected to the resistive load | 39 |
| 4.10 | Simulation result of PV module is directly connected to the resistive load at irradiance 1000 W/m ² and temperature 25 °C. | 40 |
| 4.11 | Simulation result of PV module is directly connected to the resistive load at various irradiances and temperature 25 °C. | 40 |
| 4.12 | Simulink model of P&O MPPT algorithm | 41 |
| 4.13 | Simulink model of PV module coupled with DC-DC Boost converter and P&O MPPT algorithm | 41 |
| 4.14 | Simulation result of PV module coupled with DC-DC Boost converter and P&O MPPT algorithm | 42 |
| 4.15 | Fuzzy membership functions for input E(k). | 42 |
| 4.16 | Fuzzy membership functions for input CE(k). | 43 |
| 4.17 | Fuzzy membership functions for output dD(k). | 43 |
| 4.18 | fuzzy rules surface | 43 |
| 4.19 | Simulink model for comparison of tracking power between P&O algorithm and Fuzzy Logic MPPT controller. | 44 |
| 4.20 | Comparison of tracking power between P&O algorithm and Fuzzy Logic MPPT controller at irradiance 1000 W/m ² and temperature at 25°C. | 44 |

CHAPTER 1

INTRODUCTION

1.1 Motivation

In the last years global warming and energy policies have become a hot topic on the international agenda. Developed countries are trying to reduce their greenhouse gas emissions. Renewable energy sources are considered as a technological option for generating clean energy. Among them, photovoltaic (PV) system has received a great attention as it appears to be one of the most promising renewable energy sources. Photovoltaic power generation has an important role to play due to the fact that it is a green source. The only emissions associated with PV power generation are those from the production of its components.

However, the development for improving the efficiency of the PV system is still a challenging field of research. MPPT algorithms are necessary in PV applications because the MPP of a solar module varies with the irradiation and temperature, so the use of MPPT algorithms is required in order to obtain the maximum output power from a solar array.

Therefore, the motivation of this thesis is to obtain the maximum power point (MPP) of photovoltaic (PV) system by using Fuzzy Logic Controller (FLC). Hence, this thesis focused on the well-known Perturb and Observe (P&O) algorithm and compared to a design fuzzy logic controller (FLC). A simulation work dealing with MPPT controller, a DC/DC Boost converter feeding a load is achieved. The result will show the validity of the proposed Fuzzy Logic MPPT in the PV system.

1.2 Project Background

A photovoltaic system for isolated grid-connected applications as shown in Fig. 1.0 is a typically composed of these main components:

- i. PV module that converts solar energy to electric power
- ii. DC-DC converter that converts produced DC voltage by the PV module to a load voltage demand.
- iii. Digital controller that drives the converter operation with MPPT capability.




Fig. 1.0. Typical diagram of MPPT in a PV System

1.2.1 PV Equivalent Circuit

The model of solar cell can be categorized as p-n semiconductor junction; when exposed to light, the DC current is generated. As known by many researchers, the generated current depends on solar irradiance, temperature, and load current. The typical equivalent circuit of PV cell is shown in Fig. 2.0.




Fig. 1.1 Typical circuit of PV solar cell

The basic equations describing the I-V characteristic of the PV model are given in the following equations: [11]

$$0 = I_{sc} - I_D - \frac{V_D}{R_p} - I_{PV} \dots\dots\dots(1.0)$$

$$I_D = I_0 (e^{V_D/V_T} - 1) \dots\dots\dots(1.1)$$

$$V_{PV} = V_D - R_s I_{PV} \dots\dots\dots(1.2)$$

Where:

I_{PV} is the cell current (A).

I_{SC} is the light generated current (A).

I_D is the diode saturation current (A).

R_s is the cell series resistance (ohms).

R_p is the cell shunt resistance (ohms).

V_D is the diode voltage (V).

V_T is the temperature voltage (V).

V_{PV} is the cell voltage (V).

1.2.2 PV Module Characteristic

The photovoltaic modules are made up of silicon cells. The silicon solar cells which give output voltage of around 0.7V under open circuit condition. When many such cells are connected in series we get a solar PV module. Normally in a module there are 36 cells which amount for a open circuit voltage of about 20V. The current rating of the modules depends on the area of the individual cells. Higher the cell area high is the current output of the cell. For obtaining higher power output the solar PV modules are connected in series and parallel combinations forming solar PV arrays. A typical characteristic curve of the called current (I) and voltage (V) curve and power (W) and voltage (V) curve of the module is shown in Fig.1.2




Fig.1.2 Characteristics of a typical solar PV module.

1.2.3 Need for Maximum Power Tracking

Power output of a Solar PV module changes with change in direction of sun, changes in solar insolation level and with varying temperature as shown in the Fig. 1.3&1.4.

As seen in the PV (power vs. voltage) curve of the module there is a single maximum of power. That is, there exists a peak power corresponding to a particular voltage and current. We know that the efficiency of the solar PV module is low about 13%. Since the module efficiency is low it is desirable to operate the module at the peak power point so that the maximum power can be delivered to the load under varying temperature and insolation conditions. Hence maximization of power improves the utilization of the solar PV module. A maximum power point tracker (MPPT) is used for extracting the maximum power from the solar PV module and transferring that power to the load.




Fig.1.3 Changes in the characteristics of the solar PV module due to change in insolation level.

A dc/dc converter (step up/step down) serves the purpose of transferring maximum power from the solar PV module to the load. A dc/dc converter acts as an interface between the load and the module fig.1.5. By changing the duty cycle the load impedance as seen by the source is varied and matched at the point of the peak power with the source so as to transfer the maximum power.




Fig.1.4 Change in the module characteristics due to the change in temperature




Fig.1.5 Block diagram of a typical MPPT system

1.2.4 How Maximum Power Point (MPP) is obtained.

The maximum power point is obtained by introducing a dc/dc converter in between the load and the solar PV module. The duty cycle of the converter is changed till the peak power point is obtained.

Considering a step up converter is used

$$V_o = (1/(1-D)) * V_i \dots (1.3)$$

(V_o is output voltage and V_i is input voltage)

solving for the Impedance transfer ratio

$$R_o = (1/(1-D))^2 * R_i \dots (1.4)$$

(R_o is output impedance and R_i is input impedance as seen by the source.)

$$R_i = (1-D)^2 * R_o \dots (1.5)$$

Thus output resistance R_o remains constant and by changing the duty cycle the input resistance R_i seen by the source changes. So the resistance corresponding to the peak power point is obtained by changing the duty cycle. As shown in the fig.1.6.




Fig.1.6 DC/DC converter helps in tracking the peak power point

1.2.5 Methods of Peak Power Tracking.

The peak power is reached with the help of a dc/dc converter by adjusting its duty cycle such that the resistance corresponding to the peak power is obtained. Now question arises how to vary the duty cycle and in which direction so that peak power is reached. Whether manual tracking or automatic tracking? Manual tracking is not possible so automatic tracking is preferred to manual tracking. An automatic tracking can be performed by utilizing various algorithms.

- i. Perturb and observe [3],[4],[7].
- ii. Incremental Conductance [5],[9].
- iii. Parasitic Capacitance [9].
- iv. Voltage Based Peak Power Tracking [9].

- v. Current Based peak power Tracking [9].
- vi. Computational Intelligent (e.g. fuzzy logic, neural network) [1],[2]

The algorithms are implemented in a microcontroller or a personal computer to implement maximum power tracking. The algorithm changes the duty cycle of the dc/dc converter to maximize the power output of the module and make it operate at the peak power point of the module. P&O and fuzzy logic algorithm are explained in detailed in the chapter 3.

1.3 Problem Statement

When a PV module is directly coupled to a load, the PV module's operating point will be at the intersection of its I-V curve and the load line which is the I-V relationship of load.




Fig. 1.7 PV module is directly connected to a (variable) resistive load.

In Fig. 1.7, a resistive load has a straight line with a slope of $1/R_{\text{load}}$ as shown in Fig. 1.8. In other words, the impedance of load dictates the operating condition of the PV module. In general, this operating point is seldom at the PV module's MPP, thus it is not producing the maximum power.




Fig. 1.8 I-V curve of PV module and various resistive loads

To mitigate this problem, a maximum power point tracker (MPPT) can be used to maintain the PV module's operating point at the MPP. MPPTs can extract more than 97% of the PV power when properly optimized [51].

1.4 Project Objectives

The objectives of this project are:-

- i. To track the maximum power point (MPP) of PV module by using Fuzzy Logic MPPT controller.
- ii. To simulate and analyse the performance of Fuzzy Logic MPPT controller with other conventional controller.

1.5 Project Scopes

The scopes of this project are:-

- i. To develop a SIMULINK model of PV module that converts solar energy to electric one.
- ii. To develop a SIMULINK model of DC-DC boost converter that converts produced DC voltage by the PV module to a load voltage demand.
- iii. To develop a SIMULINK model of Fuzzy Logic Controller (FLC) that drives the converter operation with MPPT capability.



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

CHAPTER 2

LITERATURE REVIEW

The following literature survey for the current report consists of various papers published in the IEEE conferences and the journals.

[1]. Control of DC/DC Converters for Solar Energy System with Maximum Power Tracking. [4].

Chihchiang Hua and Chihming Shen.

The object of this paper is to analyze and design DC/DC converters of different types in a solar energy system to investigate the performance of the converters. A simple method which combines a discrete time control and a PI compensator is used to track the Maximum power points (MPP's) of the solar array. The system is kept to operate close to the MPPT's, thus the maximum possible power transfer from the solar array is achieved. The implementation of the proposed converter system was based on a digital signal processor (DSP). Experimental tests were carried out for buck, boost and buck-boost converters using a simple maximum power point tracking (MPPT) algorithm. The efficiencies for the system with different converters are compared. The paper is used full in evaluating the response of step up, step down converter for the MPPT system.

REFERENCES

- [1] Subiyanto, A Mohamed, M A Hannan, "Maximum Power Point Tracking in Grid Connected PV System Using A Novel Fuzzy LogicController", *IEEE Student Conference on Research and Development*, November 2009.
- [2] L Chun-Hua, Z. Xin- Jian, S. Sheng, and H Wan-Qi, "Maximum Power Point Tracking Of A Photovoltaic Energy System UsingNeural Fuzzy Techniques," *Journal Shanghai University* Vol 13 (1) : 29-36, 2009.
- [3].ChihchiangHua, ,Jongrong Lin, and ChihmingShen,"Implementation of a DSPControlledPhotovoltaic System with Peak Power Tracking",IEEE TRANSACTIONS ONINDUSTRIAL ELECTRONICS, VOL. 45, NO. 1, FEBRUARY 1998 pp 99-107.
- [4].ChihchiangHua and ChihmingShen, "Control of DC/DC Converters for Solar EnergySystem with Maximum Power Tracking".
- [5]. K. H. Hussein *et al*, "Maximum Photovolatic Power Tracking: An Algorithm forrapidly changing atmospheric conditions," *Proc. Inst. Elect. Eng.* vol. 142, pt. G, no. 1,pp. 59–64, Jan. 1995.
- [6].C.R. Sullivan and M.J. Powers,"A High-Efficiency Maximum Power Point Trackingfor Photovoltaic Arrays in a Solar-Power Race Vehicle", IEEE PESC'93, 1993, pp.574-580.
- [7].B.K. Bose, P.M. Szczesny and R.L. Steigerwald,,"Microcomputer Control of aResidential Photovoltaic Power Conditioning System", IEEE Trans. on IndustryApplications, vol. IA-21, no. 5,Sep. 1985, pp1182-1191.
- [8].Xuejun Liu and A.C.Lopes,,"An Improved Perturbation and Observe Maximum PowerPoint Tracking Algorithm for PV Arrays"IEEE PESC '2004, pp.2005-2010.
- [9].D. P. Hohm, M. E. Ropp,"Comparative Study of Maximum Power Point TrackingAlgorithms Using an Experimental, Programmable, Maximum Power Point TrackingTest Bed",IEEE,2000,pp.1699-1702.
- [10]. Mohammad A. S. Masoum, HoomanDehbonei, and Ewald F. Fuchs, "Theoreticaland Experimental Analyses of Photovoltaic Systems With Voltage- and

Current-Based Maximum Power-Point Tracking”, IEEE TRANSACTIONS ON ENERGY CONVERSION, VOL. 17, NO. 4, DECEMBER 2002.

[11] Pongsakorn Takun, Somyot Kaitwanidvilai and Chaiyan Jettanasen, “Maximum Power Point Tracking using Fuzzy Logic Control for Photovoltaic Systems,” in *Proc. International Multi Conference Of Engineers and Computer Scientists 2011 vol . II, IMECS 2011, March 16-18, 2011, Hong Kong*

[12] Mayssa Farhat and Lassaad Sbata, “Advanced Fuzzy MPPT Control Algorithm for Photovoltaic Systems,” *Science Academy Transactions on Renewable Energy Systems Engineering and Technology* Vol. 1, No. 1, March 2011, United Kingdom

[13] M. G. Villalva and E. R. Filho, “Modeling and circuit-based simulation of photovoltaic arrays,” *Brazilian Journal of Power Electronics*, vol. 14, no. 1, pp. 35–45, May, 2009.

[14] J. A. Gow and C. D. Manning, “Development of a photovoltaic array model for use in power-electronics simulation studies,” *IEE Proc. Elect. Power Appl.*, vol. 146, no. 2, pp. 193–200, 1999.

[15] J. A. Gow and C. D. Manning, “Development of a model for photovoltaic arrays suitable for use in simulation studies of solar energy conversion systems,” in *Proc. 6th Int. Conf. Power Electron. Variable Speed Drives*, 1996, pp. 69–74.

[16] N. Pongratananukul and T. Kasparis, “Tool for automated simulation of solar arrays using general-purpose simulators,” in *Proc. IEEE Workshop Comput. Power Electron.*, 2004, pp. 10–14.

[17] S. Chowdhury, G. A. Taylor, S. P. Chowdhury, A. K. Saha, and Y. H. Song, “Modelling, simulation and performance analysis of a PV array in an embedded environment,” in *Proc. 42nd Int. Univ. Power Eng. Conf. (UPEC)*, 2007, pp. 781–785.

[18] J. Hyvarinen and J. Karila, “New analysis method for crystalline silicon cells,” in *Proc. 3rd World Conf. Photovoltaic Energy Convers.*, 2003, vol. 2, pp. 1521–1524.

[19] K. Nishioka, N. Sakitani, Y. Uraoka, and T. Fuyuki, “Analysis of multicrystalline silicon solar cells by modified 3-diode equivalent circuit model taking leakage current through periphery into consideration,” *Solar Energy Mater. Solar Cells*, vol. 91, no. 13, pp. 1222–1227, 2007.

- [20] C. Carrero, J. Amador, and S. Arnaltes, "A single procedure for helping PV designers to select silicon PV module and evaluate the loss resistances," *Renewable Energy*, vol. 32, no. 15, pp. 2579–2589, Dec. 2007.
- [21] E. Koutroulis, K. Kalaitzakis, and V. Tzitzilonis, (2008). Development of a FPGA-based system for real-time simulation of photovoltaic modules, *Microelectron. J.* [Online].
- [22] G. E. Ahmad, H. M. S. Hussein, and H. H. El-Ghetany, "Theoretical analysis and experimental verification of PV modules," *Renewable Energy*, vol. 28, no. 8, pp. 1159–1168, 2003.
- [23] G. Walker, "Evaluating MPPT converter topologies using a matlab PV model," *J. Elect. Electron. Eng., Australia*, vol. 21, no. 1, pp. 45–55, 2001.
- [24] M. Veerachary, "PSIM circuit-oriented simulator model for the nonlinear photovoltaic sources," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 42, no. 2, pp. 735–740, Apr. 2006.
- [25] A. N. Celik and N. Acikgoz, "Modelling and experimental verification of the operating current of mono-crystalline photovoltaic modules using four- and five-parameter models," *Appl. Energy*, vol. 84, no. 1, pp. 1–15, Jan. 2007.
- [26] Y.-C. Kuo, T.-J. Liang, and J.-F. Chen, "Novel maximum-power-point tracking controller for photovoltaic energy conversion system," *IEEE Trans. Ind. Electron.*, vol. 48, no. 3, pp. 594–601, Jun. 2001.
- [27] M. T. Elhagry, A. A. T. Elkousy, M. B. Saleh, T. F. Elshatter, and E. M. Abou-Elzahab, "Fuzzy modeling of photovoltaic panel equivalent circuit," in *Proc. 40th Midwest Symp. Circuits Syst.*, Aug. 1997, vol. 1, pp. 60–63.
- [28] S. Liu and R. A. Dougal, "Dynamic multiphysics model for solar array," *IEEE Trans. Energy Convers.*, vol. 17, no. 2, pp. 285–294, Jun. 2002.
- [29] Y. Yusof, S. H. Sayuti, M. Abdul Latif, and M. Z. C. Wanik, "Modeling and simulation of maximum power point tracker for photovoltaic system," in *Proc. Nat. Power Energy Conf. (PEC)*, 2004, pp. 88–93.
- [30] D. Sera, R. Teodorescu, and P. Rodriguez, "PV panel model based on datasheet values," in *Proc. IEEE Int. Symp. Ind. Electron. (ISIE)*, 2007, pp. 2392–2396.

- [31] M. A. Vitorino, L. V. Hartmann, A. M. N. Lima, and M. B. R. Correa, "Using the model of the solar cell for determining the maximum powerpoint of photovoltaic systems," in *Proc. Eur. Conf. Power Electron. Appl.*, 2007, pp. 1–10.
- [32] D. Dondi, D. Brunelli, L. Benini, P. Pavan, A. Bertacchini, and L. Larcher, "Photovoltaic cell modeling for solar energy powered sensor networks," in *Proc. 2nd Int. Workshop Adv. Sens. Interface (IWASI)*, 2007, pp. 1–6.
- [33] H. Patel and V. Agarwal, "MATLAB-based modeling to study the effects of partial shading on PV array characteristics," *IEEE Trans. Energy Convers.*, vol. 23, no. 1, pp. 302–310, Mar. 2008.
- [34] W. Yi-Bo, W. Chun-Sheng, L. Hua, and X. Hong-Hua, "Steady-state model and power flow analysis of grid-connected photovoltaic power system," in *Proc. IEEE Int. Conf. Ind. Technol. (ICIT'08)*, pp. 1–6.
- [35] K. Khouzam, C. Khoon Ly, C. Koh, and P. Y. Ng, "Simulation and real time modeling of space photovoltaic systems," in *Proc. IEEE 1st World Conf. Photovoltaic Energy Convers., Conf. Record 24th IEEE Photovoltaic Spec. Conf.*, 1994, vol. 2, pp. 2038–2041.
- [36] M. C. Glass, "Improved solar array power point model with SPICE realization," in *Proc. 31st Intersoc. Energy Convers. Eng. Conf. (IECEC)*, Aug. 1996, vol. 1, pp. 286–291.
- [37] I. H. Altas and A. M. Sharaf, "A photovoltaic array simulation model for matlab-simulink GUI environment," in *Proc. Int. Conf. Clean Elect. Power (ICCEP)*, 2007, pp. 341–345.
- [38] E. Matagne, R. Chenni, and R. El Bachtiri, "A photovoltaic cell model based on nominal data only," in *Proc. Int. Conf. Power Eng., Energy Elect. Drives, POWERENG*, 2007, pp. 562–565.
- [39] Y. T. Tan, D. S. Kirschen, and N. Jenkins, "A model of PV generation suitable for stability analysis," *IEEE Trans. Energy Convers.*, vol. 19, no. 4, pp. 748–755, Dec. 2004.
- [40] A. Kajihara and A. T. Harakawa, "Model of photovoltaic cell circuits under partial shading," in *Proc. IEEE Int. Conf. Ind. Technol. (ICIT)*, 2005, pp. 866–870.

- [41] N. D. Benavides and P. L. Chapman, "Modeling the effect of voltage ripple on the power output of photovoltaic modules," *IEEE Trans. Ind. Electron.*, vol. 55, no. 7, pp. 2638–2643, Jul. 2008.
- [42] W. De Soto, S. A. Klein, and W. A. Beckman, "Improvement and validation of a model for photovoltaic array performance," *Solar Energy*, vol. 80, no. 1, pp. 78–88, Jan. 2006.
- [43] Q. Kou, S. A. Klein, and W. A. Beckman, "A method for estimating the long-term performance of direct-coupled PV pumping systems," *Solar Energy*, vol. 64, no. 1–3, pp. 33–40, Sep. 1998.
- [44] A. Driesse, S. Harrison, and P. Jain, "Evaluating the effectiveness of maximum power point tracking methods in photovoltaic power systems using array performance models," in *Proc. IEEE Power Electron. Spec. Conf. (PESC)*, 2007, pp. 145–151.
- [45] R. A. Messenger and J. Ventre, *Photovoltaic Systems Engineering*. Boca Raton, FL: CRC Press, 2004.
- [46] F. Nakanishi, T. Ikegami, K. Ebihara, S. Kuriyama, and Y. Shiota, "Modeling and operation of a 10 kW photovoltaic power generator using equivalent electric circuit method," in *Proc. Conf. Record 28th IEEE Photovoltaic Spec. Conf.*, Sep. 2000, pp. 1703–1706.
- [47] J. Crispim, M. Carreira, and R. Castro, "Validation of photovoltaic electrical models against manufacturers data and experimental results," in *Proc. Int. Conf. Power Eng., Energy Elect. Drives, POWERENG*, 2007, pp. 556–561.
- [48] K. H. Hussein, I. Muta, T. Hoshino, and M. Osakada, "Maximum photovoltaic power tracking: An algorithm for rapidly changing atmospheric conditions," in *Proc. IEE Proc.-Generation, Transmiss. Distrib.*, Jan. 1995, vol. 142, pp. 59–64.
- [49] Muhammad H. Rashid, "Power Electronics Circuits, Devices and Applications", Third Edition.
- [50] Modelling and Control design for DC-DC converter, Power Management group, AVLSI Lab, IIT-Kharagpur.
- [51] Hohm, D.P., Ropp, M.E., 2002. Comparative study of maximum power point tracking algorithms. *Progress in Photovoltaics: Research and Applications*, 47–62.

- [52]. Eram, T., Chapman, P.L., 2007. Comparison of photovoltaic array maximum power point tracking techniques. IEEE Transactions on Energy Conversion 22 (2), 439–449.

